

SPECIFICATIONS FOR
DETACHABLE DROP DECK LOWBOY

(Deminsions are approximate)

(Deck must be 26 ft. min.)

Y_ N_ 55 TON CAPACITY GAWR

Y_ N_ 50,000lb. WEBS

Y_ N_ 50 inch LOADED 5th WHEEL HEIGHT

Y_ N_ 26 ft. CLEAR DECK LENGTH min.

Y_ N_ 18 inch LOADED DECH HEIGTH WITH 6 inch GROUND CLEARANCE

Y_ N_ SET UP FOR WET LINE OPERATION

Y_ N_ J560 7 PIN ELECTRICAL CONNECTOR

Y_ N_ DECK 8ft. 6 inch OVERALL WIDTH

Y_ N_ COVERED TOOL BOX TRAYS

Y_ N_ MANUAL FRONT APPROACH RAMPS

Y_ N_ EXTENSION BRACKETS REMOVABLE SWING TYPE

Y_ N_ FRONT BOGIE RAMPS

Y_ N_ 3 AXEL 25,000 NOMINAL CAPACITY

Y_ N_ AXEL SPREAD 54.5 inches

Y_ N_ AIR RIDE SUSPENSION

Y_ N_ BRAKES 16 ½ X 7 inch WITH AUTOMATIC SLACK ADJUSTERS

Y_ N_ WHEELS 8.25 X 22.5

Y_ N_ TIRES 275 / 70 X 22.5 16 ply

Y_ N_ SEALED ELECTRICAL HARNESS

Y_ N_ DOT SEALED BEAM LED LIGHTS

Y_ N_ 4 inch FLUSH MOUNT BATTERY OPERATED STROBE LIGHTS

Y_ N_ 38 D RINGS

Y_ N_ FLAG HOLDERS FRONT AND REAR

Y_ N_ APPROXIMATE DRY WEIGHT 22,000 lbs.

Y_ N_ POLYURETHANE PAINT PREFERABLY BLACK

Y_ N_ WET KIT FOR TRUCK, PUMP, TANK, LINES ETC.

Y_ N_ APPROXIMATE LENGTH OF TRAILER 52ft min.

Y_ N_ APITONG FLOORING PREFERED

Y_ N_ RIDE HEIGHT CONTROL SYSTEM WITH DUMP VALVE

Y_ N_ REFLECTIVE MARKERS SIDES AND FRONT

Dimensions ARE APPROXIMATE
Must have 26+ Foot Lower Deck

